

# product data sheet

## VARCHAIN RANGE

### Chainsaw Lubricants

**Varchain** lubricants are available in a range of viscosity grades to suit varied applications requiring a “low fling” lubricant

**Varchain** lubricants contain extreme pressure and antiwear additives together with high molecular weight polymers to resist breakdown and displacement of the lubricant even under high loads.

**Varchain** lubricants are recommended for chainsaw cutter bars, open roller chain lubrication, roller bearings and are also suitable for general machine lubrication where non drip characteristics are required.

### Features & Benefits

- Outstanding anti-wear/EP properties
- Protects against rust and corrosion
- Formulated on high quality mineral oil
- Resistant to chain fly off

### Typical Data

<b>Varchain</b>	<b>68</b>	<b>150</b>	<b>220</b>	
ISO Grade	68	150	220	
Viscosity @40°C	69.2	148.9	218.1	mm <sup>2</sup> /s
Flashpoint (PMOC)	200	200	200	°C (min)
Pourpoint	-8	-8	-8	°C (max)
Specific Gravity @20°C	0.88	0.89	0.89	

### Operational Recommendations

**Varchain** lubricants are designed to be used as supplied. Containers should always be stored indoors and protected from extremes of temperature.

A separate MSDS is available for this product. Additional advice can also be obtained from your local representative.

This publication contains information and recommendations based upon data obtained from sources considered reliable and believed to be correct, however, no warranty or guarantee is expressed or implied.