

product data sheet

VARCLEAN TFR 100

Traffic Film Remover and Multipurpose Degreaser

Varclean TFR 100 is a multipurpose cleaner/degreaser formulated using high foaming surfactants, cleaning agents and alkalis for the removal of general dirt, traffic film and grease from vehicles and machinery.

Varclean TFR 100 has been developed for vehicle bodywork and machinery cleaning. Care should be taken when used at strong concentrations on polished aluminium.

Varclean TFR 100 can be diluted up to 100:1 depending on amount of road traffic film to be removed and hardness of local water. Application can be via pressure wash or brush and rinsed with clean water.

Applications

- Removal of dirt, grease, traffic film and grime
- Bodywork
- Tautliner - curtain sided trailers
- Chassis
- Vans, Buses, Trucks
- Painted surfaces
- Floors and walls

Features & Benefits

- Excellent performance characteristics
- High dilution ratio 100:1
- Coloured product to aid selection and use
- Contains high foam surfactants and metasilicates
- Suitable for use with all types of vehicle cleaning systems
- High performance for arduous applications

Directions for use

- Brush Application 1%-1.5% ■ High Pressure Washer 1% – 2%
- Adjust dilution depending on water hardness and pressure washer type
- When using pressure washer allow 5 minutes for activation before rinsing with clean water
- Shelf life 3 years from date of manufacture
- In use at 100:1 pH 10.0 to 11.0
- Store sealed in a cool dry place between 5°C and 30°C
- For guidance on handling and disposal please refer to the Material Safety Data Sheet

Varclean TFR 100

Characteristics	Typical Data	Characteristics	Typical Data
Appearance	Amber liquid ^{oo}	Specific Gravity (@20°C)	1.09
Odour	Characteristic	PH (@ 1% concentration)	10.0 – 11.0
Solubility	Soluble in Water	PH (as supplied)	13.0 – 14.0
Flammability	Non Flammable		