

product data sheet

VARPLANT HYTRANS UTTO

Universal Tractor Transmission Oil

Varplant Hytrans UTTO is blended from carefully selected base oils and the very latest in additive technology to produce a specialised lubricant to meet the latest and most severe transmission requirements. It meets the demands of most agricultural transmission specifications and greatly reduces wet brake noise and chatter. It offers outstanding anti wear performance under the most severe conditions.

Varplant Hytrans UTTO is not suitable for use in engines. Available in red or undyed.

Features & Benefits

- Outstanding anti-wear protection
- Helps reduce wet brake noise and chatter
- Excellent low temperature properties
- Reduces Brake Chatter and Squawk
- Provides High Gear Wear Protection
- Enhances Hydraulic Operation
- Designed for Universal Applications

Specifications

■ API	GL-4	■ MASSEY FERGUSON	M1135/1143/1145
■ JOHN DEERE	J20C/J20A	■ API	GL-4
■ ALLISON	C4	■ CAT	T0-2
■ KUBOTA	UDT	■ FORD	M2C-134D/86-B
■ VOLVO	WB101/97303	■ NEW HOLLAND	NH 420A/410B
■ ZF	TE-ML03E/05F/06K/ 17E/21F	■ VALTRA	G2-08

Varplant Hytrans UTTO

Characteristics	Typical Data	Characteristics	Typical Data
Specific Gravity (@15°C)	0.883	Viscosity Index	141
Kinematic Viscosity, 40 °C	62 cSt	Kinematic Viscosity, 100 °C	9.8 cSt
Pour Point	-38 °C	Flash Point COC	220 °C