

product data sheet

VARPLANT MULTIFARM 15w30

Universal Tractor Oil

Varplant Multifarm 15w30 can be used in four stroke, naturally aspirated and turbo-charged diesel engines and four stroke petrol engines fitted on farm machinery, where it provides good standards of engine cleanliness and protection for components. The product performs well in hydraulic systems, where it protects pumps, system components and rams against wear and corrosion. It is formulated to release entrained air and help prevent sponginess in system operation.

Varplant Multifarm 15w30 can also be used in hydrostatic transmissions on tractors, combine harvesters, where a universal type product is recommended by the manufacturer and where oil immersed or wet brakes may be fitted.

Features & Benefits

- Excellent Thermal Stability
- Suitable for many agricultural machinery requirements
- Reduced Fuel Consumption
- Low Drag Formulation and reduced Friction
- Rapid Circulation on Start-up
- Excellent Anti-wear and potential bearing Corrosion Protection
- Reduces Oil Inventory
- Minimises squark and chatter
- Meets a range of OEM requirements
- Lower Emissions
- Resists Black Sludge, lacquer and deposit formation
- Engine Cleanliness
- Low Oil Consumption
- Environmentally friendly low Chlorine Formulation

Specifications

■ API	CF-4/SF	■ MASSEY FERGUSON	M1139
■ FORD	M2C-159B	■ API	GL-4
■ ALLISON	C4	■ CAT	T0-2

Varplant Multifarm 15w30

Characteristics	Typical Data	Characteristics	Typical Data
Specific Gravity (@15°C)	0.884	Viscosity Index	141
Kinematic Viscosity, 40 °C	81 cSt	Kinematic Viscosity, 100 °C	11.5 cSt
Pour Point	-30 °C	Flash Point COC	163 °C