

product data sheet

VARCHAIN 150

High Performance Chain Lubricant

VARCHAIN 150 contains extreme pressure and anti-wear additives together with high molecular weight polymers to resist breakdown and displacement of the lubricant even under high loads.

VARCHAIN 150 is suitable for applications that require a low fling lubricant.

VARCHAIN 150 is recommended for chainsaw cutter bars, open roller chain lubrication, roller bearings and are also suitable for general machine lubrication where non drip characteristics are required.

Features and Benefits

Formulated on high quality mineral oil

Outstanding anti-wear/EP properties

Protects against rust and corrosion

Resistant to chain fly off

Typical Data

Parameter	Unit of measure	Result
ISO Grade	-	150
Kinematic Viscosity @ 40°C	mm²/Sec	150.00
Specific Gravity @ 15.5°C	g/cm³	0.890
Flash point (PMOC)	°C	200
Pour point	°C	-21

product data sheet

Applications

Suitable in all types of pressure fed chainsaws

Varchain oils are typically used as supplied. **Varchain** oils should always be stored indoors and protected from extremes of temperature.

Additional Products

Varchain ISO 100 - 220	A range of traditional chainsaw lubricants available in various viscosities.	Varchain BIO ISO 68 - 220	A range of biodegradable chainsaw lubricants offering excellent environmental benefits.
Varplant Hytrans UTTO	Universal Tractor Transmission oil	Varclean TFR	A caustic based traffic film remover available in various strengths.
Varplant Multifarm	A universal multi-grade oil suitable for many four stroke, naturally aspirated and turbo-charged diesel engines	Varol Truck Wash	A versatile alkaline floor and hard surface cleaner. It will also perform as a general degreaser, chassis cleaner and traffic film remover
Varplant 2 Stroke Syntho	Synthetic 2 stroke engine oil	Varplant Lawn 30	SAE30 Lawnmower oil