

product data sheet

VARFLEET HD SAE10

Monograde mineral based engine oil

Varfleet HD SAE10 are premium monograde engine oils based on high quality mineral oils and additives that provide protection from thermal breakdown.

Varfleet HD SAE10 are suitable for normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercials vehicles, plant, compressor, industrial and certain hydraulic and transmission applications

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Reduces sludge formation providing cleaner engines
Excellent high temperature stability and reduced oxidation
Excellent anti-wear protection for reduced engine wear.
Miscible with all synthetic and mineral based engine oils

Specifications

API CG-4 / CF-4
MB 228.3
ACEA E2
MAN M3275



oroduct data sheet

Typical Data				
Parameter	Unit of measure	Result		
Viscosity Grade		SAE10W		
Kinematic Viscosity @ 40°C	mm²/Sec	34.23		
Kinematic Viscosity @ 100°C	mm²/Sec	5.65		
Viscosity index	-	102		
Pour point	°C	-27		
Specific Gravity	g/cm³	0.880		
Appearance	-	Clear and bright		
Colour	-	Amber		
TBN	mgKOH/g	9.0		

Additional Products				
Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.	
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash	