

product data sheet

VARFLEET HD SAE30

Monograde mineral based engine oil

Varfleet HD SAE30 are premium monograde engine oils based on high quality mineral oils and additives that provide protection from thermal breakdown.

Varfleet HD SAE30 are suitable for normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercials vehicles, plant, compressor, industrial and certain hydraulic and transmission applications

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Reduces sludge formation providing cleaner engines
Excellent high temperature stability and reduced oxidation
Excellent anti-wear protection for reduced engine wear.
Miscible with all synthetic and mineral based engine oils

Specifications

API	CG-4 / CF-4
MB	228.3
ACEA	E2
MAN	M3275

product data sheet

Typical Data		
Parameter	Unit of measure	Result
Viscosity Grade		SAE30
Kinematic Viscosity @ 40°C	mm²/Sec	94.60
Kinematic Viscosity @ 100°C	mm²/Sec	11.05
Viscosity index	-	101
Pour point	°C	-27
Specific Gravity	g/cm³	0.884
Appearance	-	Clear and bright
Colour	-	Amber
TBN	mgKOH/g	9.0

Additional Products			
Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash