

product data sheet

VARFLEET HD SAE50

Monograde mineral based engine oil

Varfleet HD SAE50 are premium monograde engine oils based on high quality mineral oils and additives that provide protection from thermal breakdown.

Varfleet HD SAE50 are suitable for normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercials vehicles, plant, compressor, industrial and certain hydraulic and transmission applications

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Reduces sludge formation providing cleaner engines
Excellent high temperature stability and reduced oxidation
Excellent anti-wear protection for reduced engine wear.
Miscible with all synthetic and mineral based engine oils

Specifications

API CG-4 / CF-4
MB 228.3
ACEA E2
MAN M3275



oroduct data sheet

Typical Data				
Parameter	Unit of measure	Result		
Viscosity Grade		SAE50		
Kinematic Viscosity @ 40°C	mm²/Sec	220.15		
Kinematic Viscosity @ 100°C	mm²/Sec	20.48		
Viscosity index	-	108		
Pour point	°C	-30		
Specific Gravity	g/cm³	0.892		
Appearance	-	Clear and bright		
Colour	-	Amber		
TBN	mgKOH/g	9.0		

Additional Products				
Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.	
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash	