

product data sheet

VARSYNTH SYNTHO 10W30

Petrol and Diesel Semi Synthetic Engine Oil

VARSYNTH SYNTHO 10W30 is a high performance multigrade engine oil meeting the latest API classifications. Present day motor engineering and motoring conditions have necessitated the rapid development on lubricant design and performance. The advanced additive system and base oil selection ensures high product integrity and therefore meets the requirements of the majority of engine manufacturers requirements and specifications.

VARSYNTH SYNTHO 10W30 is suitable for normally aspirated and turbo charged highly stressed petrol engines and diesel engines in passenger cars, heavy commercials, vans, plant, buses and industrial equipment. It is miscible with synthetic and mineral based engine oils.

Not designed for vehicles equipped with diesel particulate filter after treatment devices

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

- High shear stability for stay in grade performance
- Excellent high temperature stability
- Improved bore polishing protection
- Excellent anti-wear performance for reduced engine wear
- Ideal mixed fleet lubricant
- Excellent sludge control for stop-go city motoring

Specifications

API
ACEA

SN/CF
A3/B3 A3/B4

product data sheet

Typical Data		
Parameter	Unit of measure	Result
Viscosity Grade		10w30
Kinematic Viscosity @ 40°C	mm²/Sec	71.00
Kinematic Viscosity @ 100°C	mm²/Sec	11.00
Viscosity index	-	146
Pour point	°C	-33
Specific Gravity	g/cm³	0.876
Appearance	-	Clear and bright
Colour	-	Amber

Additional Products			
Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash