

product data sheet

VARSYNTH ULTRA 5W30 FD

High Performance Synthetic Engine Oil

Varsynth Ultra 5w30 FD is a fuel efficient SAE 5W-30 Synthetic Engine Oil meeting Ford M2C913-D for Euro 5 and 6 Ford engines

Varsynth Ultra 5w30 FD engine oil is formulated for Ford Diesel and Gasoline engines to meet Euro 5 and 6 emission legislation. The product has been developed to meet the latest Ford engine technology using wet timing belts. The grade is also backwards compatible with Ford engines requiring 912-D, 913-A/B/C.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Provides excellent fuel economy

100 % Synthetic Mid Saps technology giving excellent performance.

Stay in grade formulation that gives extended drain intervals

Designed to prevent the build of sludge and dirt to maintain engine performance

Fully compatible with all mineral and synthetic oil types

Outstanding resistance to oxidation

High film strength under all operating conditions

Specifications

API SL/CF ACEA A5/B5

FORD M2C912-A, 913A,B,C FORD Ford WSS-M2C913-D



oroduct data sheet

Typical Data				
Parameter	Unit of measure	Result		
Viscosity Grade		5w30		
Kinematic Viscosity @ 40°C	mm²/Sec	64.20		
Kinematic Viscosity @ 100°C	mm²/Sec	10.93		
Viscosity index	-	162		
Pour point	°C	-45		
Specific Gravity	g/cm³	0.856		
Appearance	-	Clear and bright		
Colour	-	Amber		

Additional Products				
Varsynth Ultra	A range of semi- synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.	
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash	