

product data sheet

VARTRANS 85W140 GL5

Mineral oil based GL4 / GL5 gear oil

Vartrans 85w140 GL5 is a multigrade gear oil meeting GL-4 / GL5 specification.

Vartrans 85w140 GL5 are formulated from high quality paraffin base oils and high performance extreme pressure additives that give excellent protection against wear.

Vartrans 85w140 GL5 are intended to be used in automotive vehicles including industrial and commercial vehicles.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Suitable for synchromesh gear boxes
Exceptional resistance to oxidation
Long service life
Outstanding low and high temperature performance.
Covers API GL-5 and GL-4 offering rationalisation of grades

Specifications

API	GL-4 / GL-5
-----	-------------

product data sheet

Typical Data		
Parameter	Unit of measure	Result
Viscosity Grade		85w140
Kinematic Viscosity @ 40°C	mm²/Sec	325.00
Kinematic Viscosity @ 100°C	mm²/Sec	27.04
Viscosity index	-	110
Pour point	°C	-17
Specific Gravity	g/cm³	0.900
Appearance	-	Clear and bright
Colour	-	Amber

Additional Products			
Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash