

product data sheet

VARTRANS SYNTHO 75W80

Fully Synthetic GL4 / GL5 gear oil

Vartrans Syntho 75w80 is a premium multigrade gear oil meeting GL-4 / GL5 specification.

Vartrans Syntho 75w80 are formulated from high quality synthetic base oils and high performance extreme pressure additives that give excellent protection against wear.

Vartrans Syntho 75w80 are intended to be used in automotive vehicles including industrial and commercial vehicles.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Suitable for synchromesh gear boxes
Exceptional resistance to oxidation
Long service life
Outstanding low and high temperature performance.
Covers API GL-5 and GL-4 offering rationalisation of grades

Specifications

API

GL-4 / GL-5 / MT-1

product data sheet

Typical Data		
Parameter	Unit of measure	Result
Viscosity Grade		75w80
Kinematic Viscosity @ 40°C	mm²/Sec	54.02
Kinematic Viscosity @ 100°C	mm²/Sec	9.12
Viscosity index	-	151
Pour point	°C	-39
Specific Gravity	g/cm³	0.860
Appearance	-	Clear and bright
Colour	-	Amber

Additional Products			
Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash