

Shelah Road Halesowen West Midlands B63 3PN United Kingdom T: 0121 550 3443 F: 0121 585 5405

## product data sheet

### VARTRANS TO4 SAE 10

Off Highway Transmission and Hydraulic Oil

**VARTRANS TO4 SAE 10** is formulated with high quality mineral oils and additives designed to provide the correct frictional characteristics required by Caterpillar in transmission and hydraulic systems. The additive system also gives this oil improved temperature performance, superior resistance to oxidation, rust, corrosion and improved anti-foam properties. In addition these grades have excellent extreme pressure (EP) and anti-wear characteristics ensuring maximum frictional material life in power shift transmissions

**VARTRANS TO4 SAE 10** is designed for use in a wide variety of Caterpillar construction and material handling equipment. Applications include: power shift transmissions, direct drive transmissions, winches, final drives for track-type tractors (pipe layers, skidders, loaders, excavators, etc.) and wheeled tractors (loaders, compactors, graders, etc.) and certain hydraulic systems.

**VARTRANS TO4 SAE 10** has outstanding wet brake performance, eliminating "squawk and chatter" and prolonging component life.

#### **Key Features**

Reduces sludge formation.

Excellent high temperature stability and reduced oxidation.

Excellent anti-wear protection for reduced wear.

May also be used in Allison and ZF power shift transmissions, manual transmissions and torque converters, where an oil of this type and specification is required. Provides protection if accidentally used in an engine.

#### Specifications

| Caterpillar | TO-4         |  |
|-------------|--------------|--|
| Allison     | C-4          |  |
| API         | MT-1         |  |
| ZF          | TE-ML 03C    |  |
| Komatsu     | KES 07.861.1 |  |
|             |              |  |

# www.varollubricants.com



Shelah Road Halesowen West Midlands B63 3PN United Kingdom T: 0121 550 3443 F: 0121 585 5405

## product data sheet

| Typical Data                |                   |                  |  |  |
|-----------------------------|-------------------|------------------|--|--|
| Parameter                   | Unit of measure   | Result           |  |  |
| Viscosity Grade             |                   | SAE 10W          |  |  |
| Kinematic Viscosity @ 40°C  | mm²/Sec           | 37.85            |  |  |
| Kinematic Viscosity @ 100°C | mm²/Sec           | 5.95             |  |  |
| Viscosity index             | -                 | 98               |  |  |
| Pour point                  | °C                | -27              |  |  |
| Specific Gravity            | g/cm <sup>3</sup> | 0.880            |  |  |
| Appearance                  | -                 | Clear and bright |  |  |
| Colour                      | -                 | Amber            |  |  |

| Additional Products |   |                      |  |  |  |
|---------------------|---|----------------------|--|--|--|
| Varsynth Ultra      | A range of semi &<br>synthetic engine oils<br>available in a wide<br>range of specifications. | Vartrans             | A range of automotive<br>gear and transmission<br>oils available in both<br>mono and multi-grade<br>viscosities. |  |  |
| Varol Anti-freeze   | Available in<br>concentrated form and<br>also pre-mixed ready<br>for use.                     | Varol Screen<br>Wash | High performance<br>commercial screen wash   |  |  |

# www.varollubricants.com