

product data sheet

VARTRANS SYNTHO 75W140

Fully Synthetic GL4 / GL5 gear oil

Vartrans Syntho 75w140 is an advanced heavy duty synthetic multigrade gear oil meeting GL 4 / GL5 specification.

Vartrans Syntho 75w140 are formulated from high quality synthetic base oils and high performance extreme pressure additives that give excellent protection against wear.

Vartrans Syntho 75w140 are intended to be used in automotive vehicles including industrial and commercial vehicles.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

Key Features

Exceptional resistance to oxidation
Long service life
Outstanding low and high temperature performance.
Covers API GL-5 and GL-4 offering rationalisation of grades

Specifications

API GL-4 / GL-5

product data sheet

Typical Data		
Parameter	Unit of measure	Result
Viscosity Grade		75w140
Kinematic Viscosity @ 40°C	mm²/Sec	184.00
Kinematic Viscosity @ 100°C	mm²/Sec	24.60
Viscosity index	-	165
Pour point	°C	-43
Specific Gravity	g/cm³	0.866
Appearance	-	Clear and bright
Colour	-	Amber

Additional Products

Varsynth Ultra	A range of semi & synthetic engine oils available in a wide range of specifications.	Vartrans	A range of automotive gear and transmission oils available in both mono and multi-grade viscosities.
Varol Anti-freeze	Available in concentrated form and also pre-mixed ready for use.	Varol Screen Wash	High performance commercial screen wash